

# command - setCellProperties

Set cell properties of the cell in which the caret or selection is positioned.

## Parameters:

Name	Type	Description
actionName	String	'setCellProperties' cell properties setting API
properties	Object	{ border: {Object}, style: {Object}, tableHead: {Object} }

## Example:

```
// Set cell border style
editor.execCommand('setCellProperties', {
  border: {
    style: 'dotted', // 'solid', 'dotted', 'dashed', 'double'
    width: 5, // px
    color: { r: 0, g: 0, b: 255 },
    select: [true, true, true, true, true] // top, middle, bottom, left, center, right
  }
});

// Set cell to table header
editor.execCommand('setCellProperties', {
  tableHead: {
    scope: 'none', // 'none', 'row', 'col'
    tagName: 'th' // 'th', 'td'
  }
});

// Set cell background color
editor.execCommand('setCellProperties', {
  style: {
    backgroundColor: { r: 255, g: 0, b: 0 }
  }
});

// Set vertical align of cell
editor.execCommand('setCellProperties', {
  style: {
    verticalAlign: 'middle' // 'top', 'middle', 'bottom'
  }
});

// Set horizontal align of cell
editor.execCommand('setCellProperties', {
  style: {
    align: 'right' // 'left', 'center', 'right', 'justify'
  }
});
```