

Installing Import Server

Requirements

- OS : Windows, Linux
- Platform : Java 8 or above

Changing Settings

Change "_s_INSTALLPATH_s_" to the actual installation path.

Modifying config-properties

Windows	Linux
<ul style="list-style-type: none">• SynapDocViewServer/config-properties.xml	<ul style="list-style-type: none">• SynapDocViewServer/config-properties.xml
SynapDocViewServer/config-properties.xml	SynapDocViewServer/config-properties.xml
<pre><entry key="convert.config.baseDir" >_s_INSTALLPATH_s_\\baseDir</entry> <entry key="convert.config.downloadDir" >_s_INSTALLPATH_s_\\down</entry> <entry key="convert.config.outputDir" >_s_INSTALLPATH_s_\\out</entry> <entry key="convert.config.skinDir" >_s_INSTALLPATH_s_\\baseDir\\skin</entry> <entry key="convert.config.workingDir" >_s_INSTALLPATH_s_\\work</entry> <entry key="watermark.watermarkDir" >_s_INSTALLPATH_s_\\watermark</entry></pre>	<pre><entry key="convert.config.baseDir" >_s_INSTALLPATH_s_/baseDir</entry> <entry key="convert.config.downloadDir" >_s_INSTALLPATH_s_/down</entry> <entry key="convert.config.outputDir" >_s_INSTALLPATH_s_/out</entry> <entry key="convert.config.skinDir" >_s_INSTALLPATH_s_/baseDir/skin</entry> <entry key="convert.config.workingDir" >_s_INSTALLPATH_s_/work</entry> <entry key="watermark.watermarkDir" >_s_INSTALLPATH_s_/watermark</entry></pre>
ex) <entry key="convert.config.baseDir">c:\\SynapDocViewServer\\baseDir</entry>	ex) <entry key="convert.config.baseDir">/home/user/SynapDocViewServer/baseDir</entry>

Modifying catalina

Windows	Linux
<ul style="list-style-type: none">• SynapDocViewServer/tomcat/bin/catalina.bat	<ul style="list-style-type: none">• SynapDocViewServer/tomcat/bin/catalina.sh
SynapDocViewServer/tomcat/bin/catalina.bat	SynapDocViewServer/tomcat/bin/catalina.sh
<pre>rem set CONVERT_DIR_PATH=-Dconfig.dir.path= _s_INSTALLPATH_s_</pre>	<pre>#JAVA_OPTS="\$JAVA_OPTS -Dconfig.dir. path='_s_INSTALLPATH_s_'</pre>
Remove annotations (rem)	Remove annotations (#)
ex) set CONVERT_DIR_PATH=-Dconfig.dir.path="c:\\SynapDocViewServer\\"	ex) JAVA_OPTS="\$JAVA_OPTS -Dconfig.dir.path="/home/user/SynapDocViewServer/"
ex) set "JAVA_OPTS=%JAVA_OPTS% %CONVERT_DIR_PATH%"	

Replacing Converter Module

Copy the converter module and fonts folder and paste them under "SynapDocViewServer/baseDir/bin/".

Windows	Linux
sedocConverter.exe libeay32.dll libxml2.dll libxslt.dll zlibwapi.dll	sedocConverter_exe

Starting Database

Windows	Linux
Run "SynapDocViewServer/hsql/hsql_db_startup.bat"	Run "SynapDocViewServer/hsql/hsql_db_startup.sh"

Running Tomcat (8080 port)

Windows	Linux
Run "SynapDocViewServer/tomcat/bin/startup.bat"	Run "SynapDocViewServer/tomcat/bin/startup.sh"

Confirmation

It is a success if the admin page is successfully displayed when you access <http://localhost:8080/SynapDocViewServer/admin>.