

Set Basic Editing Style

It is the feature to designate the default styles to each editing elements and render in inline-style. It can be used to define the default style for editing or initialize influence of upper CSS.

Style Designating Method

'editor.defaultStyle': Designate the default style to the desired model element type.

- You may designate styles only to the designated model element types.
- The style can be designated in the form of cssText string.

Example of Designating Default Style

synapeditor.config.js

```
'editor.defaultStyle': {  
  'Body': 'font-family: Arial, Helvetica, sans-serif; font-size: 11pt; line-height: 1.2;',  
  'Paragraph': 'line-height: 1.4'  
},
```

Result of Designating Default Style

```
<div class="se-contents" style="font-family: Arial, Helvetica, sans-serif; font-size: 11pt; line-height:  
1.2; padding: 25px;">  
  <p style="margin-right: 0px; margin-bottom: 16px; margin-left: 0px; display: block;">  
    <span>Designating Default Style</span>  
  </p>  
  <p style="margin-right: 0px; margin-bottom: 16px; margin-left: 0px; display: block;">  
    <span>Designating Default Style</span>  
  </p>  
</div>
```

Supported Model Element Type

Model Element Type	Description
Body	Refers to the editing window (div.se-contents).
Paragraph	Refers to <p> tag.
TextRun	Refers to tag.
Div	Refers to <div> tag.
Image	Refers to tag.
Video	Refers to <video> tag.
List	Refers to tag.
ListItem	Refers to tag.
Quote	Refers to <blockquote> tag.
Table	Refers to <table> tag.
TableRow	Refers to <tr> tag.
TableCell	Refers to <td> tag.
HorizontalLine	Refers to <hr> tag.
Iframe	Refers to <iframe> tag.

See also

- [Custom Styles](#)