

# getTextByRegex

RELEASE 2.3.0 OR ABOVE

Load the text information that corresponds with the given regular expression from Synap Editor.

## Parameters:

Name	Type	Description
regex	Object	Regular expression for the text to load

## Return:

Type	Attribute	Description
Array	[ { id: "paragraphId1", text: "+Article 1 (Purpose)" }, { id: "paragraphId2", text: "+Article 2 (Definition)" }, .... ]	paragraph id of the paragraph in which the text is located and the text

## Example:

```
var textInfoList = editor.getTextByRegex(/+\d+([-s\d\w]+)/g);
```

## Example

## Sample of Inserting a Bookmark through getTextByRegex

Move the caret using "**setCaretById**" Selection API that moves the caret based on the paragraph ID and insert the bookmark using "**insertBookmark**" bookmark inserting EDIT API, with the text found by the regular expression as the bookmark ID.

## Example:

```
var textInfoList = editor.getTextByRegex(/+\d+([-s\d\w]+)/g);
/* return value
[
    { id: "paragraphId1", text: "+Article 1 (Purpose)" },
    { id: "paragraphId2", text: "+Article 2 (Definition)" },
    ....
]
*/
textInfoList.forEach(textInfo => {
    editor.execCommand('setCaretById', textInfo.id);
    editor.execCommand('insertBookmark', textInfo.text);
});
```

- You may create a table of contents hyperlinks using the generated bookmarks.