

beforeOpenDocument

2.3.0

().

: API

```
var editorId = 'synapEditor';
var editorConfig = {};
var html = '';
var editor = new SynapEditor(editorId, editorConfig, html);

editor.setEventListener('beforeOpenDocument', function (e) {
});
```

:

```
var editorId = 'synapEditor';
var editorConfig = {};
var html = '';

function SynapEditorBeforeOpenDocument(e) {
}

new SynapEditor(editorId, editorConfig, html);
```

:

```
var editorId = 'synapEditor';
var editorConfig = {};
var html = '';
var eventListeners = {
  beforeOpenDocument: function (e) {
  }
};

new SynapEditor(editorId, editorConfig, html, eventListeners);
```

e

e

```
// release 2.3.0
{
  editor: SynapEditor,
  eventType: 'beforeOpenDocument',
  cancelable: true,
  returnValue: null,
  fileType: 'WORD', // ('HTML', 'WORD', 'CELL', ...)
  fileName: 'filename.docx' //
}

// release 2.14.6
{
  editor: SynapEditor,
  eventType: 'beforeOpenDocument',
  cancelable: true,
  returnValue: null,
  fileType: 'WORD',
  fileName: 'filename.docx',
  fileSize: 100 // [2.14.6] (: Byte)
}
```

API

event.setApi(api)

2.7.0

API .

```
{
  beforeOpenDocument: function (e) {
    e.setApi('newImportURL');
  }
}
```

event.setFileFieldName(fileFieldName)

2.7.0

form data fieldName .(: 'file')

```
{
  beforeOpenDocument: function (e) {
    e.setFileFieldName('file');
  }
}
```

event.addHeader(key, value)

2.7.0

Request Header .

```
{
  beforeOpenDocument: function (e) {
    e.addHeader('X-Hello', 'World');
  }
}
```

event.addParameter(key, value)

2.7.0

Parameter .

```
{
  beforeOpenDocument: function (e) {
    e.addParameter('hello', 'world');
  }
}
```