

Partial Editing Restrictions

The partial editing restriction function is a method of restricting all or part of a document from being editable.

Assignable target element

Model	Tag
Body	<div class='se-content'>
Div	<div>
Table	<table>
TableCell	<td>

How to specify

Using source code

Assign `se-lock` and `se-unlock` classes to the corresponding element in the source view.

Set lock, unlock

```
<div class="se-contents" style="font-family: Arial, Helvetica, sans-serif; font-size: 11pt; line-height: 1.2; padding: 25px;">
  <table class="se-lock">
    <tr>
      <td>1</td>
      <td class="se-unlock">2 - unlock</td>
    </tr>
    <tr>
      <td>3</td>
      <td>4</td>
    </tr>
  </table>
</div>
```

Using API

Set lock, unlock

```
<script>
    window.editor.setLock('#lock-table');
    window.editor.setUnlock('#unlock-cell');
</script>

<div class="se-content" style="font-family: Arial, Helvetica, sans-serif; font-size: 11pt; line-height: 1.2;
padding: 25px;">
    <table id="lock-table">
        <tr>
            <td>1</td>
            <td id="unlock-cell">2 - unlock</td>
        </tr>
        <tr>
            <td>3</td>
            <td>4</td>
        </tr>
    </table>
</div>
```

Rules of operation

1. Selection works regardless of lock/unlock.
2. If the lock is set, the child element cannot be edited.
3. The unlock is only meaningful if the parent element is locked.
4. Child Element can be edited if unlock is set.

Experience

- [Experience partial editing restrictions](#)