# **Events**

- Event Type
   Adding Events

   Using API
   Adding at the Editor Initialization
   Using Functions

   Removing Events

   Using API

   Object Delivered by Functions
   Cancelling Events

## **Event Type**

Event Name	Version	Description
initialized	RELEASE 2.1.0 OR ABOVE	This event occurs when the Editor is initialized.
beforeUploadImage	RELEASE 2.2.0 OR ABOVE	This event occurs before an image is uploaded.
afterUploadImage	RELEASE 2.2.0 OR ABOVE	This event occurs after an image is uploaded.
beforeUploadVideo	RELEASE 2.2.0 OR ABOVE	This event occurs before a video is uploaded.
afterUploadVideo	RELEASE 2.2.0 OR ABOVE	This event occurs after a video is uploaded.
beforeUploadFile	RELEASE 2.2.0 OR ABOVE	This event occurs before a file is uploaded.
afterUploadFile	RELEASE 2.2.0 OR ABOVE	This event occurs after a file is uploaded.
beforeOpenDocume nt	RELEASE 2.3.0 OR ABOVE	This event occurs before a document is opened (imported).
afterOpenDocument	RELEASE 2.3.0 OR ABOVE	This event occurs after a document is opened (imported).
beforeNewDocument	RELEASE 2.4.1 OR ABOVE	This event occurs before creating a new document.
afterNewDocument	RELEASE 2.4.1 OR ABOVE	This event occurs after creating a new document.
onSelection	RELEASE 2.6.0 OR ABOVE	This event occurs when performing a selection operation such as moving the caret and expanding the selection.
beforePaste	RELEASE 2.10.0 OR ABOVE	This event occurs before pasting.
afterPaste	RELEASE 2.10.0 OR ABOVE	This event occurs after pasting.
afterEdit	RELEASE 2.10.0 OR ABOVE	This event occurs after all editing actions.

## Adding Events

### **Using API**

#### editor.setEventListener()

API used to add an event.

```
editor.setEventListener('Event Name', function(e) {
});
```

#### Adding at the Editor Initialization

```
var editorId = 'synapEditor';
var editorConfig = {};
var html = '';
var eventListeners = {
    'Event Name': function (e) {
    }
};
new SynapEditor(editorId, editorConfig, html, eventListeners);
```

#### **Using Functions**

```
var editorId = 'synapEditor';
var editorConfig = {};
var html = '';

function SynapEditorEvent Name(e) {
    // The first letter of the event name shall be capitalized
    // ex: initialized => SynapEditorInitialized
    // ex: beforeUploadImage => SynapEditorBeforeUploadImage
}

new SynapEditor(editorId, editorConfig, html);
```

### Removing Events

#### Using API

#### editor.removeEventListener()

API used to remove an event..

```
editor.removeEventListener('Event Name');
```

### Object Delivered by Functions

```
editor: {Editor Object}, // Editor
eventType: 'initialized', // Event Name
cancelable: false, // Whether the event is cancelable
returnValue: null, // Return Value
....
}
```

- editor: Editor in which the event is occurred.
- eventType: Event name.
- cancelable: Whether the event is cancelable.

• returValue: Return value. As for cancelable events, the events can be cancelled by delivering (cancelable: true) false.

## **Cancelling Events**

When cancelable is set to true, you may cancel the event by setting returnValue to false.