

Quote

Quote extends [Element](#)

The API model used to edit quotation marks.

Methods

- [append\(html\)](#)
- [prepend\(html\)](#)
- [remove\(\)](#)
- [replace\(html\)](#)
- [setHTML\(html\)](#)
- [setText\(text\)](#)

append(html)

- `html <String>` HTML String to append.

The HTML String passed as an argument is added as a child at the back of the Element.

```
var quote = editor.getAPIModelById('id');
quote.append(' <span>TEXT</span>');
```

prepend(html)

- `html <String>` HTML String to append.

The HTML String passed as an argument is added as a child to the front of the Element.

```
var quote = editor.getAPIModelById('id');
quote.prepend(' <span>TEXT</span>');
```

remove()

Removes the Element itself.

IF ALL ELEMENTS ARE REMOVED, ERRORS MAY OCCUR IN SUBSEQUENT OPERATIONS.

```
var quote = editor.getAPIModelById('id');
quote.remove();
```

replace(html)

- `html <String>` The HTML String to replace.

Replaces the element itself with the HTML String passed as an argument.

```
var quote = editor.getAPIModelById('id');
quote.replace(' <p><span>Quote replaced</span></p>');
```

setHTML(html)

- `html <String>` HTML string to set inside quotes

HTML HTML .

```
var quote = editor.getAPIModelById('id');
quote.setHTML(' <p><span>Add HTML. All previously entered information will be erased.</span></p>');
```

setText(text)

- text <String> Text string to set inside quotation marks

Set the text string value passed as an argument to the internal text of quotation marks.

```
var quote = editor.getAPIModelById('id');  
quote.setText('Sample text.');
```