

command - setTableProperties

Set table properties of the table in which the caret or selection is positioned.

Parameters:

Name	Type	Description
actionName	String	'setTableProperties' table properties setting API
properties	Object	{ style: {Object}, caption: {Object}, head: {Object}, ..}

Example:

```
// Set table caption
editor.execCommand('setTableProperties', {
  caption: {
    position: 'top',    // 'none', 'top', 'bottom'
    text: ' '
  }
});

// Set table header
editor.execCommand('setTableProperties', {
  head: {
    scope: false,
    value: 'row' // 'none', 'row', 'col', 'both'
  }
});

// Set table border style
editor.execCommand('setTableProperties', {
  style: {
    border: {
      style: 'dotted', // 'solid', 'dotted', 'dashed', 'double'
      width: 10, // px
      color: { r: 255, g: 0, b: 0 }
    }
  }
});

// Set table width and height
editor.execCommand('setTableProperties', {
  style: {
    width: { value: 800, unit: 'px' },
    height: { value: 300, unit: 'px' }
  }
});

// Set table align
editor.execCommand('setTableProperties', {
  style: {
    blockAlign: 'center' // 'left', 'center', 'right'
  }
});

// Set table other properties
editor.execCommand('setTableProperties', {
  style: {
    tableLayout: 'auto', // 'auto', 'fixed'
    display: 'table' // 'table', 'inline-table'
  }
});
```