

Body

Body extends [Element](#)

The API model used to edit the Body area. In Synap Editor, the body area is composed of `<div class='se-contents'></div>`.

Methods

- [append\(html\)](#)
- [prepend\(html\)](#)
- [replace\(html\)](#)
- [setHTML\(html\)](#)
- [setText\(text\)](#)

append(html)

- `html` `<String>` HTML String to append.

The HTML String passed as an argument is added as a child at the back of the Element.

```
var body = editor.getAPIModels('.se-contents')[0];
body.append(' <p><span>APPEND TEXT</span></p>' );
```

prepend(html)

- `html` `<String>` HTML String to prepend.

The HTML String passed as an argument is added as a child to the front of the Element.

```
var body = editor.getAPIModels('.se-contents')[0];
body.prepend(' <p><span>PREPEND TEXT</span></p>' );
```

replace(html)

- `html` `<String>` The HTML String to replace.

Replaces the element itself with the HTML String passed as an argument.

```
var body = editor.getAPIModels('.se-contents')[0];
body.replace(' <p><span>Body replaced</span></p>' );
```

setHTML(html)

- `html` `<String>` HTML string to set

Sets the HTML string value passed as an argument to the body's internal HTML.

```
var body = editor.getAPIModels('.se-contents')[0];
body.setHTML(' <p><span>Add HTML to the body. All previously entered information will be erased.</span></p>' );
```

setText(text)

- `text` `<String>` Text string to set

Set the text string value passed as an argument to the internal text of the body.

```
var body = editor.getAPIModels('.se-contents')[0];
body.setText('Add text to the body. All previously entered information will be erased.');
```