

Quote

Quote extends Element

The API model used to edit quotation marks.

Methods

- `append(html)`
- `prepend(html)`
- `remove()`
- `replace(html)`
- `setHTML(html)`
- `setText(text)`

append(html)

- `html <String>` HTML String to append.

The HTML String passed as an argument is added as a child at the back of the Element.

```
var quote = editor.getAPIModelById('id');
quote.append('<span>TEXT</span>');
```

prepend(html)

- `html <String>` HTML String to append.

The HTML String passed as an argument is added as a child to the front of the Element.

```
var quote = editor.getAPIModelById('id');
quote.prepend('<span>TEXT</span>');
```

remove()

Removes the Element itself.

IF ALL ELEMENTS ARE REMOVED, ERRORS MAY OCCUR IN SUBSEQUENT OPERATIONS.

```
var quote = editor.getAPIModelById('id');
quote.remove();
```

replace(html)

- `html <String>` The HTML String to replace.

Replaces the element itself with the HTML String passed as an argument.

```
var quote = editor.getAPIModelById('id');
quote.replace('<p><span>Quote replaced</span></p>');
```

setHTML(html)

- `html <String>` HTML string to set inside quotes

HTML `HTML`.

```
var quote = editor.getAPIModelById('id');
quote.setHTML('<p><span>Add HTML. All previously entered information will be erased.</span></p>');
```

setText(text)

- text <String> Text string to set inside quotation marks

Set the text string value passed as an argument to the internal text of quotation marks.

```
var quote = editor.getAPIModelById('id');
quote.setText('Sample text.');
```