

beforeUploadVideo

2.2.0

...

: API

```
var editorId = 'synapEditor';
var editorConfig = {};
var html = '';
var editor = new SynapEditor(editorId, editorConfig, html);

editor.setEventListener('beforeUploadVideo', function (e) {
});
```

:

```
var editorId = 'synapEditor';
var editorConfig = {};
var html = '';

function SynapEditorBeforeUploadVideo(e) {
}

new SynapEditor(editorId, editorConfig, html);
```

:

```
var editorId = 'synapEditor';
var editorConfig = {};
var html = '';
var eventListeners = {
  beforeUploadVideo: function (e) {
  }
};

new SynapEditor(editorId, editorConfig, html, eventListeners);
```

e

e

```
// release 2.2.0
{
    editor: SynapEditor,
    eventType: 'beforeUploadVideo',
    cancelable: true,
    returnValue: null,
    fileName: 'filename.mp4' //
}

// release 2.2.1
{
    editor: SynapEditor,
    eventType: 'beforeUploadVideo',
    cancelable: true,
    returnValue: null,
    fileType: 'video', // [2.2.1]
    fileName: 'filename.mp4',
    uploadCount: 0 // [2.2.1] ( )
}

// release 2.14.6
{
    editor: SynapEditor,
    eventType: 'beforeUploadVideo',
    cancelable: true,
    returnValue: null,
    fileType: 'video',
    fileName: 'filename.mp4',
    fileSize: 100, // [2.14.6] (: Byte)
    uploadCount: 0
}
```

API

event.setApi(api)

2.7.0

API .

```
{
  beforeUploadVideo: function (e) {
    e.setApi('newUploadURL');
  }
}
```

event.setFileFieldName(fileFieldName)

2.7.0

form data fieldName . (: 'file')

```
{
  beforeUploadVideo: function (e) {
    e.setFileFieldName('file');
  }
}
```

event.addHeader(key, value)

2.7.0

Request Header .

```
{
  beforeUploadVideo: function (e) {
    e.addHeader('X-Hello', 'World');
  }
}
```

event.addParameter(key, value)

2.7.0

Parameter .

```
{
  beforeUploadVideo: function (e) {
    e.addParameter('hello', 'world');
  }
}
```